:Azura TS

Chemistry-free Thermal Plate System

Are you looking for a high speed, trouble-free and environmentally friendly platemaking system without ANY compromise on press?

Agfa Graphics offers you :Azura TS!

Simply EXPOSE, GUM and PRINT!



Agfa Graphics' mission is to develop innovative solutions.

Building on the proven success of the ground breaking and market
leading ThermoFuse™ technology, Agfa Graphics is pleased to offer :Azura TS
- a fast and rich in contrast ecological way of making plates.

:Azura TS eliminates the processing variables that you worry about and gives you the predictable and consistent quality that you need.

:Azura TS meets the needs for commercial printing in 4-up and 8-up applications.





A breakthrough in CtP Convenience The innovative :Azura TS technology ensures simple, care-free plate production

Press a button, expose a plate!

Because there are no processing variables to worry about anymore, :Azura TS offers you consistent and reliable plates, ready for use.

The :Azura TS plate uses the innovative, proven ThermoFuse™ coating technology. This non-ablative thermal CtP technology gives consistent high-quality chemistry-free thermal CtP plates without any compromise on press.


After exposure, the :Azura TS plates are cleaned and gummed in one simple step with the :Azura Clean Out Unit (COU). This simple, compact and reliable unit requires no developer or replenisher. Nor does the COU need a range of speed settings, brush speeds, pH monitors or temperature controls. Everything is pre-set. The :Azura TS plate is ready in minutes with no possibility of image degradation or variation. Thanks to its unique concept, :Azura TS gives you reliable, consistent and care-free plate production.

Reliable Plates with Predictable Performance

:Azura TS is suitable for a wide range of commercial printing applications on both sheet-fed and web presses. It delivers razor-sharp image definition without having to change press operating conditions or working practices. It can hold up to 2-98 % screen tints at 200 LPI and 240 lpi :Sublima, depending on platesetter capability and delivers runs of up to 100.000, depending on press conditions. :Azura TS uses Agfa Graphics' "Flat Grain Technology', the high quality grained and anodised aluminium substrate that results in uncompromising press performance with fast ink roll-up and consistent ink/water balance. This shortens make ready, minimising paper waste and downtime and all this using your existing press chemistry - there is no need to change inks, founts or plate cleaners.


The end result is MORE EFFICIENCY!






Unexposed :Azura TS plate

The single layer coating contains ink accepting ThermoFuseTM pearls.



Exposed :Azura TS plate

The coating absorbs energy from the 830nm laser imaging head. The ThermoFuse™ pearls fuse firmly to each other and bond strongly to the grained and anodised aluminium base.



Gummed : Azura TS plate

Application of the gum washes away the unexposed plate areas and creates a protective gum layer.

The :Azura TS plate is now ready for printing.

Working principle

:Azura TS comprises Agfa Graphics' "Flat Grain Technology' – an electrochemically grained and anodised aluminium base that is coated with a single layer containing ink-accepting ThermoFuse™ particles, small enough to deliver razor-sharp highlight reproduction. During the exposure on standard 830nm thermal platesetters, in the image areas the coating absorbs the heat. This heat causes these particles to fuse to each other and bond firmly to the aluminium substrate. What were once individual particles, now become a solid ink-accepting image - tough enough to achieve 100.000 run lengths.

As such, the :Azura TS image formation is a 100% physical process, not a chemical one.

The non-imaged areas can now easily be removed, by washing away with the :Azura TS gum in the Clean-Out Unit. At the same time, the gum protects the hydrophilic aluminium substrate from oxidation.

The :Azura TS plates are now ready for the press where they print directly from the aluminium substrate giving the excellent lithographic latitude expected from Agfa plates – low dampening levels giving bright colours whilst using less ink.

CtP made simple

In summary, this ground breaking Chemistry-free :Azura TS CtP technology offers you:

- Non-ablative thermal plates
- Care-free platemaking
- Robustness in the press-room
- Excellent printing characteristics with no press changes required

A physical image formation, printing directly from aluminium, excellent and predictable press performance, robust plates with wide working latitude, guarantees you "CtP, made simple"!

:Azura TS

Plate Specifications				
Plate type	Non-ablative thermal - negative-working			
Coating	ThermoFuse™, 830 nm sensitive			
Gauges	0.15, 0.20, 0.24, 0.30 mm (0.006", 0.008", 0.010", 0.012")			
Substrate	High quality grained and anodised aluminium - Agfa Graphics' "Flat Grain Technology" Standard sheetfed and web sizes 200 mJ/cm2			
Sizes				
Laser energy				
Resolution*	Up to 2 - 98 % at 200 lpi — :Sublima 240 lpi (*depending on imaging conditions)			
Plate developer	Not required			
Latent image stability	Latent image stability 24 hours Plate contrast Excellent image contrast. Plates can be measured with all available densitometers and platereaders			
Plate contrast				
Storage conditions	Ambient temperatures below 50°C / 50°C not to be exceeded for >24 hours			
Run length	Up to 100.000 dependent on press conditions			
Plate baking	Not possible			

Agfa Graphics' Optimised Pressroom Chemicals Plate Cleaner :Antura CtP Plate Cleaner Washout Gum :Antura CleanGum Deletion pen or gel KP23 - KP010 - KP011 or KP012 Normal short term storage (max 7 days) RC795 Baking gum not applicable Desensitizer PlateEtch Plus Scratch Remover Reviva Plate Fountain Solutions :Azura TS is compatible with all AGFA fountain solutions Roller and blanket washes :Azura TS is compatible with all AGFA roller and blanket washes

COL	J type	:Azura C95	:Azura C125
	Mechanical Specifications		
	Plate width	min – max 200-950 mm (7.9" - 37")	min – max 200-1250 mm (7.9" - 37")
	Plate length	min – max 310-1100 mm (12.2"-43.3")	min – max 310-1100 mm (12.2"-43.3")
	Plate thickness	0.15-0.30 mm (0.006"-0.012")	0.15 - 0.30 mm (0.006" - 0.012")
	Plate speed	60cm/min (23.6" - 0.012"), fixed	60cm/min (23.6" - 0.012"), fixed

A chemical passport indicating the most appropriate chemistry is available for all AGFA plates. Not all plates are available in every region. Contact your local Agfa representative for more information.